

PROJECT:

COMMENTS :

## DATA SHEET.

### EXTREME OUTPUT VL 2835-120 LED LIGHT TAPE

## SPECIFICATIONS.

MODEL NUMBER :	E-EO/LEDTAPE/VL/2835-120/ (CW, NW or WW)
REEL LENGTH :	10M [32.8 Ft]
REEL POWER CONSUMPTION :	144 WATTS [4.4 W/ Ft]
LED QUANTITY PER REEL :	1180 LEDs [36/Ft]
MAX. CONTINUOUS CONNECTION :	10M [32.8 Ft]
MAX POWER CONSUMPTION :	144 WATTS/REEL [4.4 W/ Ft]
MIN CUTTABLE LENGTH :	50 mm [ 2" ] (6 LEDs per increment)
AVAILABLE COLOURS :	LUMEN OUTPUT ( ± 5% ) :
CCT (K) - COOL WHITE (CW) - 5800K :	5800 (K) - 520 Lm/Ft
CCT (K) - NEUTRAL WHITE (NW) - 4100K :	4100 (K) - 480 Lm/Ft
CCT (K) - WARM WHITE (WW) - 3000K :	3000 (K) - 435 Lm/Ft
LED TAPE BEAM ANGLE :	120°
OPERATING VOLTAGE :	24Vdc
L70 RATED LIFESPAN :	>50,000 HOURS
WARRANTY :	3 YEARS
DIMMABILITY :	ADDITIONAL DIMMING MODULE REQUIRED
OPERATING ENVIRONMENT :	INDOOR (EXTERIOR AVAILABLE) EXTERIOR : 11mm x 4mm SILICONE SLEEVE
POWER SUPPLY :	UL CERTIFIED 24Vdc CLASS 2
(MORE INFO AVAILABLE UPON REQUEST)	(PLUG N PLAY or HARDWIRED MODELS)



- Aluminum extrusion channel mounting options available. (More info available upon request)
- Drill into mounting channel on site for ideal installation placement.
- Highest LED Tape light output available.
- Cuttable every 6th LED ( 2" )
- Field cut easily to any 2" increment.
- Ideal for cove, edge lighting and fluorescent replacement.
- 3M adhesive backing for simple mounting of LED Tape.
- Exterior siliconed sleeved waterproof model available.
- Dimmable (Utilizing additional components) (More info available upon request)
- Plug/play connectors for daisy chainability.

## DETAILS.

